



Chelan County Fire Marshal's Office  
Fire Protection Credit Form

**Owner/Applicant name:** \_\_\_\_\_ **Address or Parcel #** \_\_\_\_\_

<b>1. Water Supply Credit</b>	<b>POINTS</b>
Property is within and served by a Fire District ( <b>Fire District provides approved water supply</b> )	6
<b>Structures not in or served by a Fire District <u>without</u></b> an approved fire sprinkler system per NFPA 13, 13R or 13D as applicable, must provide a stored water supply based on NFPA 1142.	6
<b>Structures not in or served by a Fire District <u>with</u></b> an approved fire sprinkler system per NFPA 13, 13R or 13D as applicable.	6
<b>Total Water Supply Credits (Minimum of 6 points required)</b>	

**2. Setback and Building Credits**

30ft. minimum setback from all property lines (Only 1 setback option can be selected)	1.5
60ft. minimum setback from all property lines (Only 1 setback option can be selected)	2
100ft. minimum setback from all property lines (Only 1 setback option can be selected)	2.5
Building is less than 2,000 sq. ft.	1
Monitored fire alarm with smoke detectors (may be home fire/security system)	.5
½" Gypsum board on all interior walls (creates a thermal barrier)	1
Eaves and soffits protected on the exposed underside by 2" nominal lumber or approved non-combustible materials.	.5
Gutters and downspouts are nonexistent or constructed of noncombustible material and an approved method to prevent the buildup of debris in the gutter.	.5
Exterior walls meeting one of the following: 1. Approved non-combustible material 2. Heavy timber or log construction. 3. 1-hour fire rated construction assembly. 4. Fire retardant treated wood (labeled for exterior use)	1
Underfloor meeting one of the following: 1. Enclosed to the ground with exterior walls. 2. Approved noncombustible materials, heavy timber or log construction. 3. Limited enclosure where all exposed structural columns, beams and supporting walls are protected by 1-hour fire resistive rated construction. 4. Fire retardant treated wood (labeled for exterior use).	1
Exterior Doors and Windows having a minimum of 20-minute rating (not part of 1-hour fire resistive rated construction exterior walls)	.5
Vents for attic openings, foundation or underfloor vents or other ventilation openings in vertical exterior walls and vents through roofs shall not exceed 144 square inches each. Such vents shall be covered with noncombustible corrosion-resistant mesh with openings not to exceed 1/8 <sup>th</sup> inch.	1
<b>Total Setback and Building Credits (Minimum of 4 points required)</b>	

**Total Fire Protection Credits (Minimum of 10 points required)**

**Owner/Applicant Signature:** \_\_\_\_\_ **Date:** \_\_\_\_\_